

# Technical Data Sheet

## DESCRIPTION

**Proteck Euro Full Synthetic SAE 5W-30** is a premium full synthetic engine oil engineered to meet the stringent high performance requirements of European passenger car and light duty diesel vehicles. Formulated with state-of-the-art base stocks and high performance additives, **Proteck Euro Full Synthetic SAE 5W-30** is designed to provide the highest level of engine protection available, even under the most severe operating conditions.

## PERFORMANCE FEATURES

- Promotes Clean Engines
- Excellent Cold Start Protection
- Excellent Resistance to High Temperature Oxidation Thickening
- Reduces Formation of Sludge And Varnish Deposits
- Outstanding Protection of Emissions Systems
- Minimizes Engine Wear
- Protects Against Viscosity and Thermal Breakdown
- Excellent Rust and Corrosion Protection

## APPLICATIONS

- API SL
- API CF
- ACEA A5 / B5-10
- Renault RN 700
- Mercedes Benz 229.3 / 229.5
- Volkswagen 502.00 / 505.00
- Opel GM-LL B-025
- BMW Longlife-01

## PROPERTIES

SAE Grade	5W-30
Viscosity	
cSt @ 40°C	65.3
cSt @ 100°C	10.8
Viscosity Index	156
Flash Point, °F	448
Pour Point, °F	-40
Density, lbs/gal @ 60 °F	7.13
Specific Gravity @ 60 °F	.8554
CCS Viscosity, cP (-30 °C)	6200
Noack Volatility, %	10
HTHS, mPa.s	3.2

\*Consult Owners Manual For Application Requirements